# **VIC ASH HARDWOOD**

### GL18 Vic Ash Hardwood Glulam







#### **OVERVIEW**

- Victorian Ash is named from the alpine areas of Victoria and New South Wales in which it's grown.
- A strong and stable timber that offers all-round work ability such as sanding, gluing, finishes and bending.
- Has a straight grain but may also produce fiddle-back markings and have visible gum veins.
- The heartwood ranging from pale pink to yellowish brown and is generally difficult to tell apart heartwood and sapwood.

#### **DURABILITY**

Durability Class 4 Plantation Hardwood Available in H3 treated or untreated Available Cambered (600 m radius) and Straight

#### **GRADE APPEARANCE**

A grade appearance B grade structural

#### PROPERTY

Glulam Grade GL18 Bending Strength f'b = 50MPa Tension Strength f't = 25MPa Shear Strength f's = 5.0MPaCompression Strength f'c = 50MPa Modulus of Elasticity E = 18,500MPa Modulus of Rigidity G = 1,230MPa Density 650 kg/m<sup>3</sup>

**PERFORMANCE** 

#### SIZES\*

Standard sizes are based on timber width (mm) and height (mm) measurements. Length (m) are measured in metres between 0.9m and 18.0m. Vicbeam can manufacture measurements outside standard sizes upon request.


#### W X H (Standard sizes)

65 x 120, 150, 180, 210, 240, 270, 300, 330, 360, 390, 420

85 x 120, 150, 180, 210, 240, 270, 300, 330, 360, 390, 420, 450, 480, 510, 540, 570, 600

115 x 120, 150, 180, 210, 240, 270, 300, 330, 360, 390, 420, 450, 480, 510, 540, 570, 600

135 x 120, 150, 180, 210, 240, 270, 300, 330, 360, 390, 420, 450, 480, 510, 540, 570, 600



## Orders or Enquiries

Phone: 1300 788 705 Fax: (03) 9923 6791 Email: sales@vicbeam.com.au Website: www.vicbeam.com.au

